



NOTES:

- CUSTOMER TO PROVIDE FINAL CONNECTION OF ALL UTILITIES.
- CUSTOMER TO PROVIDE FOR DISPOSAL OF ALL REMOVED EQUIPMENT AND SCRAP.
- CUSTOMER TO PROVIDE FOR CUTTING, CURBING, AND REPAIRING OF ROOF OPENINGS AND TO PROVIDE RAIN COLLARS AS REQUIRED FOR EXHAUST STACKS AND VENTS. TRIMAC TO PROVIDE CUSTOMER WITH FINAL LOCATIONS OF PENETRATIONS DURING SYSTEM INSTALLATION. UTILITY CONNECTION LOCATIONS ARE APPROXIMATE AND FINAL CONNECTION TO TRIMAC PROVIDED EQUIPMENT IS THE RESPONSIBILITY OF THE CUSTOMER.
- CUSTOMER IS RESPONSIBLE FOR OBTAINING ALL PERMITS AND LICENSES AS MAY BE REQUIRED FOR INSTALLATION AND OPERATION OF EQUIPMENT.
- CUSTOMER IS RESPONSIBLE FOR ALL TEMPORARY UTILITY SERVICES REQUIRED FOR EQUIPMENT INSTALLATION.
- CUSTOMER TO PROVIDE MANUAL SHUTOFF VALVE WITH GAS FILTER LOCATED PER NFPA 86 FOR EACH BURNER.
- ALL FLUID & GAS SERVICES TO BE EQUIPPED WITH SUITABLE SHUTOFF VALVE AT POINT OF CONNECTION.
- CUSTOMER RESPONSIBLE FOR INSURING COMPATIBILITY OF PROCESS WITH MATERIALS OF CONSTRUCTION.
- ALL UTILITY INFORMATION BASED ON PRELIMINARY INFORMATION AND SUBJECT TO CHANGE.
- SYSTEM CONSISTS OF APPROX. 160' TOTAL ENCLOSED TRACK CONVEYOR POWERED AT 3 FEET PER MINUTE. H-ATTACHMENT ON 24" COLUMNS WITH A MAXIMUM LOAD OF 125 POUNDS FOR H-ATTACHMENT. ALL HORIZONTAL TURNS ARE TO BE 2'-0" RADII.

SYSTEM UTILITY LEGEND

UTILITY	SYMBOL	QUANTITY	VOLTAGE/ PHASE	AMPERAGE	DESCRIPTION	
ELECTRICAL	(E)	1	480V/3ø	125 AMPS	SYSTEM CONTROL PANEL	
	(C)	1	120V/1ø	15 AMPS	LUBRICATOR (DEDICATED AND CONTINUOUS)	
	(E)	1	480V/3ø	60 AMPS	TEMPORARY FOR TRIMAC CONSTRUCTION	
	(E)	1	120V/1ø	15 AMPS	TEMPORARY FOR TRIMAC CONSTRUCTION	
UTILITY	SYMBOL	QUANTITY	FLOW RATE	SUPPLY PRESSURE	CONNECTION SIZE	DESCRIPTION
CITY WATER	(W)	1	-----	40-60 PSI	1 1/2"	WASHER
UTILITY	SYMBOL	QUANTITY	FLOW RATE	SUPPLY PRESSURE	CONNECTION SIZE	DESCRIPTION
COMPRESSED AIR	(A)	1	10 SCFM	80 PSI	3/4"	TEMPORARY FOR TRIMAC CONSTRUCTION
UTILITY	SYMBOL	QUANTITY	FLOW RATE	SUPPLY PRESSURE	CONNECTION SIZE	DESCRIPTION
PROPANE	(G)	1	360 CFH	-----	1"	WASHER STAGE #1 BURNER GAS TRAIN
	(D)	1	96 CFH	3-5 PSI	3/4"	DRY-OFF OVEN GAS TRAIN
	(S)	1	216 CFH	-----	1"	CURE OVEN GAS TRAIN